

# An Approach for Sensor Placement to Achieve Complete Coverage and Connectivity in Sensor Networks

Monia Techini

University of Gabes,  
National Engineering School  
of Gabes (ENIG),  
Av. Omar Ibn El Khattab  
Zerig-6029, Gabes, Tunisia  
Email: moniatec@gmail.com

Ridha Ejbali and Mourad Zaied

REGIM-Lab: REsearch Groups  
in Intelligent Machines  
BP 1173, Sfax, 3038, Tunisia  
Email: ridha\_ejbali@ieee.org  
  
Email: mourad.zaied@ieee.org

**Abstract**—The main objective required for a Wireless Sensor Network (WSN) is the positioning of the sensor nodes to form a WSN. There are two strategies for the positioning of nodes in an area of interest where some phenomena are to be monitored: deterministically or randomly. In this paper, our goal is to propose a new sensor placement technique, which is based on random distribution with coverage and connectivity constraints.

**Keywords**—Placement; Random; WSN; Coverage; Connectivity.

## I. INTRODUCTION

Recent developments could not be achieved without a change in the field of communication. Mainly Wireless Sensor Networks (WSN) and mobile computing become more and more popular. Control of environmental parameters can give rise to several applications. In the monitoring area, the WSN is deployed over a region where some phenomena have to be monitored. The nodes can be equipped with sensors to measure temperature, humidity, and gases.

A WSN consists of a number, often significant, of sensors with limited perception and communication capabilities where each node is connected to one (or sometimes several) sensors. There exist two types of sensors: homogeneous sensors, which possess the same communication and computation capabilities and heterogeneous sensors, which possess different capabilities. Determining the sensor field architecture is a key challenge in sensor resource management. Sensors have to be placed at critical locations that provide sustainable coverage.

Many works for sensors and sensor placement were done. In [1], Lin models the sensing field as a grid points. Then, he explains how to place sensors on some grid points in order to satisfy a particular quality of service based on the Simulated Annealing approach. Using the genetic algorithm, the authors in [2] propose an approach for the sensor placement problem. In [3], the Improved Particle Swarm Optimization (IPSO) algorithms have been employed to determine the optimal sensors number and configurations.

Recent works focused on relay placement algorithm to determine the set of positions which can guarantee connectivity. The main objective of the work proposed in [4] is to reduce the set of locations for the existing mobile nodes in the network to the locations of relay nodes that would ensure connectivity with the least count. A multi-objective mathematical model

is used to determine the best placement of mobile nodes for different tasks [5]. In [6], Flushing proposes a combination of exact method and heuristic method to solve the problem mentioned below. Thus, his work was based on Mixed-Integer Linear Programming (MILP) and a Genetic Algorithm (GA).

A related problem to the deployment in WSN is Art Gallery Problem (AGP) addressed by the art gallery theorem [7]. The AGP problem consists of determining the minimum number of guards to cover the interior of an art gallery. Many researches for the AGP have been discussed in literature. There exist some similarities between our sensor placement problem and the AGP, such that the guards (sensors in our case) are assumed to have similar capabilities.

As we mentioned earlier, there exist two ways for the placing of sensors with random placement or with grid-based placement. The former one is defined as a technique where nodes are deployed at random positions. The latter is defined as the one where sensors are placed exactly at pre-engineered positions. Figure 1 shows the different categories of node placement strategies.




Figure 1. Sensor node placement methodologies

On the other side, the authors in [8] classify the place-

ment strategies into static and dynamic depending on whether the optimization is performed at the time of deployment or while the network is operational, respectively. In [8], Younis assumes that the choice of the deployment scheme depends on many properties. Thus, many researches assume that for some cases, the random placement becomes the only option due to environment characteres [1] and deployment cost and time [9]. This paper focuses on the implementation of an optimal node deployment strategy based on a random placement method. The remaining part of this paper is organized as follows: Section 2 starts by summarising the problem of the sensor placement. Our sensor placement approach is then presented in Section 3. Section 4 shows the results of our procedure. Section 5 provides our conclusions.

## II. PROBLEM STATEMENT

The problem addressed in this paper has as objective to determine minimum number of sensors when the maximum of targets are covered. There are two strategies of sensor node placement: deterministic or non-deterministic (random). We assume our goal is to deploy the sensors in order to provide the connectivity and the coverage of the service area. Thus, the main objective of our approach is to ensure that the maximum of the area is covered. The authors in [10] formulate a constrained multivariable nonlinear programming problem to deploy the sensors in their locations under constraints of network lifetime and total power consumption. They propose two optimal placement strategies to this problem.

The number of the sensors is determined by taking into account both the coverage of the area of interest and the communication between sensors in the WSN. Thus, communication in a WSN is an effective and practical way to improve the system performance of WSN. This suggests that both the network connectivity and the coverage are an essential parameter which must be taken into account when positioning sensors. Each deployed sensor should be able to cover an area in order to increase the coverage in a defined region while maintaining the connectivity in the WSN.

## III. METHOD

Sensor placement can greatly impact the WSN performances, such as coverage and connectivity. The former is defined to quantify the quality of service (QoS). The latter answers the questions about the communication network in a WSN. Table I introduces the parameters used during our work.

TABLE I. PARAMETERS OF THE WSN.

<i>Parameter</i>	<i>Definition</i>
$C_i$	Node i
$R_s$	Node sensing radius
$R_c$	Node communication radius
$A$	Network area
$A_i$	Area of the Voronoi polygon for a sensor
$N$	Number of sensor nodes in the network
$C$	Coverage of the total area
$D_{i,j}$	Distance between nodes i and j
$N_e$	Maximim number of neighbors

Minimizing the number of deployed sensors and maintaining higher sensor coverage when positioning the sensors have always been a challenge, especially when the monitoring region is unknown. The aims of the present article are to implement an approach for the sensor placement problem with coverage and communication constraints. The main goal of the sensor placement approach is to determine the best placement of the sensors. In addition, the proposed algorithm aims at achieving high sensor coverage while maintaining network connectivity.

We assume that a region  $A$  is covered if there exists a sensor at position  $p$  with sensing radius  $R_s$  that contains the region  $A$  completely [1]. Thus, the ability of detection varies with the distance between the sensor  $C_i$  and the target  $T_j$  [11] [12], mathematically speaking we have:

$$D_{i,j} \leq R_s \tag{1}$$

where  $D_{i,j}$  is the distance between the position of the sensor  $C_i$  and the target  $T_j$ .

To guarantee node communication, The connectivity is assumed to be full if the distance between two sensors is less than the communication radius of the sensor. The distance is defined as the Euclidean distance between two sensors. Figure 2 shows a pseudo code of the algorithm.

**Algorithm PLACE\_SENSORS:**

```

Step 0: deploy first sensor  $C_0$  randomly
Step1: while a maximum coverage not achieved
Step2: generate a random position for sensor  $C_i$ 
    Evaluate the distance  $D_{ij}$  between  $C_i$  and  $C_j$  ( $0 \leq j < i$ )
    If exist  $C_j$  while  $D_{ij} \leq R_c$  then
        If  $C_j$ 's neighbors  $\leq N_e$ 
            Deploy  $C_i$ 
            Link  $C_i$  and  $C_j$  and go to Step1
        Else
            Go to Step2
    End
Else
    Go to Step2
End
End
    
```

Figure 2. Algorithm for sensors placement

We begin by generating a random position for the first sensor. Then, deploying the rest by taking into account a maximum coverage and connectivity in the area of interest as constraints. The number of neighbors of each deployed sensor should be less than a defined number  $N_e$  in order to ensure a sufficient distribution in the area.

Process node 1: deploys the first sensor randomly.

Process node i: node i is deployed if there is at least a link with node j ( $0 \leq j \leq i - 1$ ) and a sufficient coverage not achieved yet.

The algorithm is iterative, and it places one sensor in the sensor field during each iteration. It terminates either when a sufficient coverage of the zone is achieved.

#### IV. SIMULATION AND RESULTS

The proposed method aims at defining the initial placement of sensors. All sensors have the same deployment parameters and have the same sensing coverage ( $R_c$ ) and the same communication range ( $R_s$ ). The former helps in the detection of the designed event. The latter is introduced for the connectivity of nodes with their neighborhoods. Thus, depending on the communication range the neighborhood of a node is defined. We say that the probability of communication between two nodes varies inversely with the distance between them.

We evaluate the proposed approach via simulations (NS2). Our topology is a square with total area  $A = 20 \times 20$ ,  $A_i$  is the area of the Voronoi polygon for a sensor for a full sensing coverage and a full connectivity defined as [13]:

$$A_s(Cov, Con) = \min(2R_s^2, R_c^2) \quad (2)$$

Twenty seconds is considered as the simulation time. It should be mentioned that we assume that all links are bi-directional during simulation. The sensing range is set to 2 while the communication range is set to 4 and the maximum number of neighbors ( $N_e$ ) for each deployed sensor is set to 4. Thus, each sensor must have a number of neighbors less than  $N_e$  (fixed to 4 in our case).

We assume that the algorithm stops when the coverage  $C$  is greater than 1, we define  $C$  as the ratio of the union of all areas covered by each node and the area of the entire Region Of Interest (ROI) [9]. The coverage  $C$  helps to ensure that the region is entirely covered by the sensors when deploying them. In this work, we try to take into account the overlapping zone between nodes when calculating the area covered by the sensors. Each node is characterized by a covered area which is defined as the circular area within its sensing radius  $R_s$ .

$$C = \frac{\cup_{i=1..N} A_i}{A} \quad (3)$$

Where  $A_i$  is the area covered by the  $i$ th node,

$N$  is the total number of nodes,

$A$  stands for the area of ROI.

Our approach is used in order to determine a better methodology for sensor placement problem in a WSN. As for results, the number of sensors in the region of interest varies from 51 to 57 providing full sensing coverage and full network connectivity. We can observe that our approach outperforms Max\_Avg\_Cov [14] [15] and MIN-MISS [15] [16]. It is important to point out that in this work, we do not take into account obstacles in the ROI.

#### V. CONCLUSION

In this paper, the sensor placement problem is studied. We have formulated a new strategy for the initial sensor placement problem. We start with a random distribution of nodes with constraints of coverage and connectivity. As part of our future

work, we would extend this result to a case when there are obstacles in the ROI. Thus, we assume that the above results are practical and can be used in actual sensor network design.

#### ACKNOWLEDGMENT

The authors would like to acknowledge the financial support of this work by grants from General Direction of Scientific Research (DGRST), Tunisia, under the ARUB program.

#### REFERENCES

- [1] F. Lin and P.-L. Chiu, "A near-optimal sensor placement algorithm to achieve complete coverage-discrimination in sensor networks," *Communications Letters, IEEE* 9.1, vol. 9, 2005, pp. 43–45.
- [2] L. T.-M. E. C. Ruben Leal, Jose Aguilar and A. Rios, "An Approach for Diagnosability Analysis and Sensor Placement for Continuous Processes Based on Evolutionary Algorithms and Analytical Redundancy," *Applied Mathematical Sciences*, vol. 9, no 43, 2015, pp. 2125–2146.
- [3] M. Z. A. Bhuiyan, G. Wang, J. Cao, and J. Wu, "Sensor placement with multiple objectives for structural health monitoring," *ACM Transactions on Sensor Networks (TOSN)*, vol. 10, no 4, 2014, pp. 68–113.
- [4] K. A. Izzet F. Senturk and F. Senel, "An effective and scalable connectivity restoration heuristic for mobile sensor/actor networks," *Global Communications Conference (GLOBECOM), 2012 IEEE*, 2012, pp. 518–523.
- [5] F. Guerriero, A. Violi, E. Natalizio, V. Loscri, and C. Costanzo, "Modelling and solving optimal placement problems in wireless sensor networks," *Applied Mathematical Modelling*, vol. 35, no 1, 2011, pp. 230–241.
- [6] E. Flushing and G. Di Caro, "Exploiting synergies between exact and heuristic methods in optimization: an application to the relay placement problem in wireless sensor networks," *Bio-Inspired Models of Network, Information, and Computing Systems*, vol. 134, 2014, pp. 250–265.
- [7] J. O'Rourke, Ed., *Art Gallery Theorems and Algorithms*. Oxford University Press, 1987.
- [8] M. Younis and K. Akkaya, "Strategies and techniques for node placement in wireless sensor networks: A survey," *Ad Hoc Networks*, vol. 6, no 4, 2008, pp. 621–655.
- [9] N. Heo and P. K. Varshney, "An intelligent deployment and clustering algorithm for a distributed mobile sensor network," *Systems, Man and Cybernetics*, 2003. *IEEE International Conference on*, vol. 5, 2003, pp. 4576–4581.
- [10] P. Cheng, C.-N. Chuah, and X. Liu, "Energy-aware node placement in wireless sensor networks," *Global Telecommunications Conference, 2004. GLOBECOM'04. IEEE*, vol. 5, 2004, pp. 3210–3214.
- [11] S. S. Dhillon, K. Chakrabarty, and S. Iyengar, "Sensor placement for grid coverage under imprecise detections," *Information Fusion, 2002. Proceedings of the Fifth International Conference*, vol. 2, 2002, pp. 1581–1587.
- [12] S. Adlakha and M. Srivastava, "Critical density thresholds for coverage in wireless sensor networks," *Wireless Communications and Networking, 2003. WCNC 2003. 2003 IEEE*, vol. 3, 2003, pp. 1615–1620.
- [13] Y. Wang, Y. Zhang, J. Liu, and R. Bhandari, "Coverage, Connectivity, and Deployment in Wireless Sensor Networks," *Recent Development in Wireless Sensor and Ad-hoc Networks*, 2015, pp. 25–44.
- [14] S. S. Dhillon and K. Chakrabarty, "Sensor placement for effective coverage and surveillance in distributed sensor networks," vol. 3. *IEEE*, 2003, pp. 1609–1614.
- [15] S. M. Reda, M. Abdelhamid, O. Latifa, and A. Amar, "Efficient uncertainty-aware deployment algorithms for wireless sensor networks," in *Wireless Communications and Networking Conference (WCNC), 2012 IEEE*. *IEEE*, 2012, pp. 2163–2167.
- [16] Y. Zou and K. Chakrabarty, "Uncertainty-aware sensor deployment algorithms for surveillance applications," in *Global Telecommunications Conference, 2003. GLOBECOM'03. IEEE*, vol. 5. *IEEE*, 2003, pp. 2972–2976.